

U.S. Serial No. 09/896,565 - Seki et al.
Art Unit 3677; Attorney Docket 2019.004
Page 2

Please amend claims 1, 7, 11 and 13 as follows:

- A2
1. (Amended) A lock for a lid that opens and closes a box, wherein one of the box and the lid is a first part and the other is a second part, the lock comprising:
- a latch provided on the first part, wherein the latch engages a catch, which is on the second part, to prevent the lid from opening when the lid is closed;
 - a holding member, which moves between a locking position and an unlocking position, wherein the holding member engages the latch at the locking position and is disengaged from the latch at the unlocking position;
 - a first manipulator for opening the lid from an outer side of the box when the lid is closed, wherein the first manipulator moves the holding member from the locking position to the unlocking position;
 - a key lock mechanism, which shifts the holding member, by an externally manipulated key, between an operational position, at which movement of the holding member by the first manipulator is enabled, and a non-operational position, at which movement of the holding member by the first manipulator is disabled; and
 - a second manipulator for opening the lid from an inner side of the box when the lid is closed, wherein the second manipulator moves the holding member from the locking position to the unlocking position.
- A3
7. (Amended) A lock for a lid that opens and closes a box, the lock comprising:
- a catch extending from an inner surface of the box;
 - a latch provided on the lid, wherein the latch engages the catch to prevent the lid from opening when the lid is closed;
 - a holding member, which moves between a locking position and an unlocking position, wherein the holding member keeps the latch engaged with the catch when located at the locking position and releases the catch from the latch when located at the unlocking position;

U.S. Serial No. 09/896,565 - Seki et al.
Art Unit 3677; Attorney Docket 2019.004
Page 3

A3 a first manipulator for opening the lid from an outer side of the box when the lid is closed, wherein the first manipulator moves the holding member from the locking position to the unlocking position when enabled;

a key lock mechanism, which shifts the holding member, by an externally manipulated key, between an operational position, at which movement of the holding member by the first manipulator is enabled, and a non-operational position, at which movement of the holding member by the first manipulator is disabled; and

a second manipulator for opening the lid from an inner side of the box when the lid is closed, wherein the second manipulator moves the holding member from the locking position to the unlocking position.

A4 11. (Amended) The lock according to claim 10, further comprising a restricting member for restricting a rotation range of the rotor.

13. (Amended) A lock for a lid that opens and closes a box, the lock comprising:
a catch extending from an inner surface of the box;
a latch provided on the lid, wherein the latch engages the catch to prevent the lid from opening when the lid is closed;

a holding member, which moves between a locking position and an unlocking position, wherein the holding member keeps the latch engaged with the catch when located at the locking position and releases the catch from the latch when located at the unlocking position;

A5 a first manipulator for opening the lid from an outer side of the box when the lid is closed, wherein the first manipulator moves the holding member from the locking position to the unlocking position; and

a second manipulator formed integrally with the holding member for opening the lid from an inner side of the box when the lid is closed, wherein the second manipulator moves the holding member from the locking position to the unlocking position; and

U.S. Serial No. 09/896,565 - Seki et al.
Art Unit 3677; Attorney Docket 2019.004
Page 4

A5
a key lock mechanism, which shifts the holding member, by an externally manipulated key, between an operational position, at which movement of the holding member by the first manipulator is enabled, and a non-operational position, at which movement of the holding member by the first manipulator is disabled.
